

Quantities shown are for design purpose only.

UNIT	ASSEMBLY WT LBS/LF				
TYPE	Bar Anchor	Stud Anchor			
Α	91	102			
В	45	45			

DETAIL WITH ANCHOR STUDS

Stud $\frac{1}{8}$ x 1'-2" @

TYPE A

 $1\frac{1}{2}$ " = 1'-0"

TYPE B

For details not shown, see "Detail with Bar Anchors".

5" = 1'-0"

Note: Alternate types of anchor studs may be permitted subject to the approval of the Engineer.

ANCHOR STUD

F I	STANDARD DRAWING APPROVED BY T DELIS RELEASED BY ROBERTO LACALLE		CALIFORNIA		DIVISION OF	BRIDGE NO.	JOINT ARMOR - EXPANSION DETAIL			
	TILE XS8-040e	APPROVAL DATE	RESPONSIBLE OFFICE CHIEF RELEASE DATE 5-8-08		DEPARTMENT OF TRANSPORTATION	ENGINEERING SERVICES	POST MILE	MAX	IMUM MOVEMENT RATING = 4"	
	DS OSD 2147A (ENGLISH STAN	NDARD DRAWING "XS" BORDER REV. 01/11/08)		ORIGINAL SCALE IN INCHES FOR REDUCED PLANS	0 1 2 3	CU EA	DISREGARD PRIN EARLIER REVISIO		REVISION DATES (PRELIMINARY STAGE ONLY)	SHEET OF